

TYBOTECH

COMPUTER ACCESSORIES

www.TYBOTECH.com

PRODUCT CATALOG

RELEASE: oktober 2006



CASES

OFFICELINE

3306 - I

- 400 Watt power supply (8 cm fan)
- Dimension: 443 x 420 x 180 mm (LxWxH)

DARKLINE

4064 - CA

- 300 Watt power supply (12 cm fan)
- Dimension: 465 x 200 x 415 mm (LxWxH)

DARKLINE

6001 - C43

- 300 Watt power supply (12 cm fan)
- Dimension: 420 x 185 x 366 mm (LxWxH)

DARKLINE

3324 - CA

- 300 Watt power supply (12 cm fan)
- Dimension: 430 x 182 x 425 mm (LxWxH)

DARKLINE

3307 - CA

- 400 Watt power supply (12 cm fan)
- Super silent power supply
- Dimension: 435 x 182 x 425 mm (LxWxH)

DARKLINE

6210L - CA

- 400 Watt power supply (12 cm fan)
- Super silent power supply
- Dimension: 485 x 182 x 430 mm (LxWxH)

DARKLINE

6211L - CA

- 400 Watt power supply (12 cm fan)
- Dimension: 490 x 182 x 425mm (LxWxH)

DARKLINE

8025 - C45

- 400 Watt power supply (12 cm fan)
- Fits in all types of mainboard up to 244 mm
- Super silent power supply
- Dimension: 492 x 185 x 430 mm (LxWxH)

DARKLINE

8029 - B34

- 400 Watt power supply (12 cm fan)
- Long version metal chassis fits in all types of mainboard up to 244 mm
- Dimension: 486 x 185 x 425 mm (LxWxH)

DARKLINE

8029 - C43

- 400 Watt power supply (12 cm fan)
- Long version metal chassis fits in all types of mainboard up to 244 mm
- Dimension: 486 x 185 x 425 mm (LxWxH)

ATRIX

Atrix 9011 - B3

- 400 Watt power supply (12 cm fan)
- Built in digital display function
- Door front panel with neon lighting
- One screw for easy access to whole case
- 20/24 pin power supply connector
- Super silent power supply
- Dimension: 504 x 195 x 456mm (LxWxH)

ATRIX

Atrix 9011 - C4

- 400 Watt power supply (12 cm fan)
- Built in digital display function
- Door front panel with neon lighting
- One screw for easy access to whole case
- 20/24 pin power supply connector
- Super silent power supply
- Dimension: 504 x 195 x 456mm (LxWxH)

BRIZA

6097 - C9

- 400 Watt gold PSU (12 cm fan)
- 2 blue neon coolers
- More than 20,000 perforations for maximum cooling
- Interior of the case fully covered with a dust filter
- Super silent power supply
- Dimension: 495 x 195 x 430 mm (LxWxH)

BRIZA

6097 - CA

- 400 Watt gold PSU (12 cm fan)
- 2 blue neon coolers
- More than 20,000 perforations for maximum cooling
- Interior of the case fully covered with a dust filter
- Super silent power supply
- Dimension: 495 x 195 x 430 mm (LxWxH)

BRIZA

6079 - CA

- 400 Watt power supply (12 cm fan)
- Dimension: 475 x 194 x 445 mm (LxWxH)

BRIZA

6079 - I

- 400 Watt power supply (12 cm fan)
- Dimension: 475 x 194 x 445 mm (LxWxH)

EXTREME GAMING CASE

G8015 - black

- 400 Watt power supply (12 cm fan)
- Blue neon light on front panel
- Clips on bezel, no screws
- Gaming window with Leds transparent fan
- LCD display HDD, CPU, fan, clock indications
- Dimension: 504 x 195 x 456 mm (LxWxH)

DARKLINE

M401 - C9

- 400 Watt power supply (12 cm fan)
- Cardreader (optional)
- Dimension: 465 x 200 x 412 mm (LxWxH)

DARKLINE

M401 - C10

- 400 Watt power supply (12 cm fan)
- Cardreader (optional)
- Dimension: 465 x 200 x 412 mm (LxWxH)

Cardreader (optional)





KEYBOARDS & MICE

KB 1307

- Standard white keyboard
- Also available in black



KB 1825

- 21 Hot keys / • With ergonomic palm rest
- Available in black & white



KB 2625

- 24 Hot keys



KB 8103

- 12 Hot keys
- 2 External USB ports



MO - 002 - black

- PS2



MO - 002 - black/silver

- USB
- Retractable mouse cable



MO - 004

- PS2



Super mini mouse

- USB
- Retractable mouse cable
- Also available in black/silver



ADD-ON PRODUCTS

COMBO adapter

- 4 USB ports (3 ext. & 1 int.)
- 2 external firewire ports



FireWire adapter

- 3 external & 1 internal firewire port



FireWire adapter

- 2 external & 1 internal firewire port



4 Channel SOUND CARD



6 Channel SOUND CARD



7 Channel SOUND CARD



TV CARD TV/AV/FM

- With remote control



USB 2.0 Adapter

- 1 internal & 3 external ports



USB 2.0 Adapter

- 1 internal & 2 external ports
- With NEC-Chipset



MODEM Adapter

- 56 HSF



Serial ATA Adapter

- 2 external ports
- With cables
- Also available with RAID



SERIAL Adapter

- Serial port



PARALLEL Adapter

- Printer port



10/100 Ethernet Adapter

- 1 x RJ-45 port



Gigabit Ethernet Adapter

- 1 x RJ-45 port



NETWORKING

RJ-45 Cableboot - 20 pcs



RJ-45 Connector shielded - 50 pcs



RJ-45 Connector unshielded - 50 pcs



RJ-45 Crimping tool



FTP patch cable

- 1m / 3m / 5m / 10m / 20m



STP crosslink cable

- 1m / 3m / 5m / 10m



UTP or FTP or STP cable rol

- 305m



ADSL modem/router

- 10/100 base
- 8 ports



Switching Hub

- 10/100 base
- 8 ports
- External power



Switching Hub Pro

- 10/100 base
- 8 ports
- External power



Switching Hub Pro

- 10/100 base
- 8 ports
- Internal power



Switching Hub

- Gigabit
- 8 ports
- External power



Switching Hub

- 10/100 base
- 16 ports
- External power



Switching Hub Pro

- 10/100 base
- 16 ports
- External power



Switching Hub Pro

- 10/100 base
- 16 ports
- Internal power



Switching Hub

- 10/100 base
- 24 ports



Lan card PCI


- 10/100 base



Lan card PCI

- Gigabit base





POWER SUPPLIES

300 Watt / 8 cm fan

- 24 pins
- ATX



400 Watt / 12 cm fan

- 24 pins / ATX Version 2.03
- Silent and better ventilation
- Temperature control fan



400 Watt titanium / 12 cm fan

- 24 pins / ATX Version 2.03
- Silent and better ventilation
- Temperature control fan



500 Watt / 12 cm fan

- 24 pins / ATX Version 2.03
- Silent and better ventilation
- Temperature control fan



Serial ATA power cable



MISCELLANEOUS

Cardbus ethernet 10/100



Cardbus ethernet gigabit



Cardbus Serial RS-232

- incl. Serial cable



Cardbus Firewire IEEE1394

- 3 Ports



Cardbus USB 2.0 + Firewire

- 2 USB ports + 2 Firewire ports
- incl. Firewire cable



Cardbus USB 2.0

- 2 USB ports



Serial ATA converter kit

- IDE Harddrive to Serial M/B contents:
- Serial ATA adapter with cover
- Serial ATA 1.0 (ATA150) signal cable
- DC power Y-cable



Multiplug

- 5 outlets



Multiplug

- 6 outlets



Multiplug

- 5 outlets with coax protection



Multiplug

- 5 outlets with tel protection



Hard Disk removable frame

- ATA 133 or SATA 150
- Available in black & white



Headphone MMS-HS-1

- With microphone



Headphone MMS-HS-2

- With microphone



Microphone MMS-MP1



Microphone MMS-MP2



USB 1.1 HUB - 4 ports

- With or without Power Adapter



USB 2.0 HUB - 4 ports

- With or without Power Adapter



USB HUB + Multibox

- 4 USB 2.0 ports
- Audio, PS2 and Firewire port
- Can be used Internal & External



KVM Switch - 2 PC's

- Access 2 PC's with one keyboard, mouse and monitor
- All cables included



KVM Switch - 4 PC's

- Access 4 PC's with one keyboard, mouse and monitor
- All cables included



Mediacenter

- Internal & external usage
- Firewire, USB 2.0, card reader, ...
- Available in black & white



19-in-1 Card reader

- 5.25" & 3.5" usage



USB 24-in-1 Card Reader

- Supports all popular media types



2.5" Hard Disk enclosure - ATA



3.5" Hard Disk enclosure

- 3 types:
- SATA-to-SATA
- SATA-to-USB
- ATA-to-USB



3.5" Hard Disk enclosure



5.25" External IDE box silver



5.25" External IDE box black



VOIP phone adapter - SE-B2K

- PC-to-PC and PC-to-phone operation



VOIP phone - SE-PSW

- PC-to-PC and PC-to-phone operation



VOIP phone - SE-P1

- PC-to-PC and PC-to-phone operation



VOIP phone - SE-P4K

- Large LCD, handfree



VOIP phone - SE-P8D

- PC-to-PC and PC-to-phone operation



Wireless VOIP phone - SE-W1D

- PC-to-PC and PC-to-phone operation





SPEAKERS



- Briza speakers 1000 Watt**
- 1000 Watt PMPO
 - RMS: 20 W + 2 x 8 W
 - Frequency response 60Hz-20kHz



- MMS2-90B**
- 1000 Watt PMPO
 - RMS: 40 W
 - Frequency response 20Hz-20kHz
 - Also available in white



- MMS4-90B**
- 1200 Watt PMPO
 - RMS: 40 W
 - Frequency response 20Hz-20kHz



- MMS5-82B**
- 1800 Watt PMPO
 - RMS: 100 W



- MMS5-86B**
- 1200 Watt PMPO
 - RMS: Woofer 15W, satellite 5 x 3 W



- X7-8600**
- 1800 Watt PMPO
 - RMS: Woofer 40 W, satellite 7 x 10 W
 - Frequency response 20Hz-20kHz



- MMS-80 / 160 / 360 (3 types of speakers)**
- 80/160/360 Watt PMPO
 - RMS: 2 x 3 W / 2 x 5 W / 2 x 8 W
 - Frequency response: 30Hz-20kHz
 - Also available in white



- MMS-120B**
- 120 Watt PMPO
 - RMS: 2 x 3 W
 - Frequency response: 60Hz-20kHz



- MMS-100S**
- 100 Watt PMPO
 - RMS: 2 x 2 W
 - Frequency response: 30Hz-20kHz



CABLES

- Round flatcable ATA133**
- 0,6 m or 0,8 m



- Flatcable for floppy disk**



- Serial ATA power cable**



- Serial ATA signal cable**
- 50 cm or 80 cm



- Parallel printercable**



- Power cable**



- Power cable extension**



- Splitcable 5.25 > 2x 5.25**



- PS2 extension cable**



- USB 2.0 cable**
- 2 m / 3 m / 5 m



- USB 2.0 extension cable**
- 1,8 m / 5 m



- USB active extension cable**
- Length: 5 m



- USB 2.0 to ethernet adapter**
- RJ-45



- USB to USB netlink**



- USB to parallel port**



- USB to serial port**



- DVI to DVI**



- Analog to DVI**



VGA CARDS

- nVIDIA FXS200 (64 MB)**
- AGP



- nVIDIA 6600LE (128 / 256 MB)**
- PCIE



- nVIDIA 7300LE (128 / 256 MB)**
- PCIE



- nVIDIA 7300GT (256 / 512 MB)**
- PCIE



- ATI Radeon 9250 7300LE (64 MB)**
- AGP



- ATI Radeon X550 7300LE (128 / 256 MB)**
- AGP



nVIDIA

